EVERDIGM Attachment Multiprocessor & Pulverizer



Tools that make people move

Multiprocessor & Pulverizer Series Turning your job into more value!

Multiprocessor



fully reversible rectangular blac

adjustment by using one set of adjust nut

Crushing low set For the primary demolition operations. Bringing down the main structure of a building.

Demoltion jaw set Specially designed and engineered for mixed concrete and steel applications, combining the advantages of shear jaw set and concrete jaw set. Processing heavily reinforced concrete structures and concrete encased i-beam steel barrels without jaw change.



Crushing

Demolition

Pulverizing jaw set

Starting to process the demolished materials. Separating reinforcing bar from concrete for example.

Shear jaw set

The shear jaw set can be used on all industrial demolition sites section bars, pipes, tanks railway



Shearing

Pulverizer Fixed type



Pulverizer for professional demolition Fixed style Pulverizer for secondary demolition

Features and benefits

on the outer of jaw for high productivity during pulverizing job

Tooth bolting style for quick and effective replacement (welding type is also available)

Hardened teeth made of special materials for enhanced durability

Integrated speed up valve delivering easy maintenance and roomy space

Trunnion type cylinder for maximum breaking force throughout jaw closing motion as well as opning motion

Produced with increased power and durability by state-of-the-art technology, EVERDIGM Pulverizers have been designed for both primary demolition work, secondary concrete reduction and material sorting.

Trunnion - supported cylinder

EVERDIGM's improved pulverizer with trunnion - supported cylinder gives you high breaking forces throughout the entire working cycle as well stable movement

Wider jaw

With its wider jaw, exceptional closing force and short cycle times, the EHP pulverizer provides excellent productivity in concrete reduction and reinforced steel separation

Durability

Increased durability has been achieved with the use of abrasive-resistant materials. Advanced design and construction produce a powerful and durable attachment to handle the toughest jobs.

Integrated speed up valve with cylider

Maximum maintenance efficency

Replaceable tooth system

Fastand effortless replacement of tooth allowing high productivity

Pulverizer Rotatable type



Pulverizer for professional demolition

The everdigm EHP series of multiprocessors feature interchangeable jaw sets mounted on a single base unit providing the effciency of four tools in one

Features and benefits

Wide jaw opening for a large demolition work surface

Hardened teeth made of special materials for enhanced durability

Hydraulic 360 rotation unit allowing fast and targeted positioning to materials

Trunnion-supported type cylinder for maximum breaking force throughout the entire operation

Integrated speed up valve with cylinder delivering easy maintenance and roomy space

Produced with increased power and durability by state-of-the-art technology, EVERDIGM Pulverizers have been designed for both primary demolition work, secondary concrete reduction and material sorting.

Integrated speed up valve with cylinder Maximum maintenance efficiency

Hydraulic 360 rotation unit Limitless rotation for fast and

targeted positioning in all conditions

Trunnion supported cylinder EVERDIGM's improved pulverizer

with trunnion supported cylinder gives you high breaking forces throughout the entire working cycle as well as stable movement

Wider jaw

With its wider jaw, exceptional closing force and short cycle times, the EHP pulverizer provides excellent productivity in concrete reduction and reinforced steel separation

Durability

Increased durability has been achieved with the use of abrasive-resistant materials. Advanced design and construction produce a powerful and durable attachment to handle the toughest jobs.

Specifications

ltem	Unit	EHC13 EHC22		EHC32			EHC40					
Jaw type		S	D	С	D	Р	S	С	D	Ρ	S	S
Working weight ¹⁾	kg	1,250	1,300	2,040	2,050	2,210	1,880	3,030	3,001	3,130	2,990	4,400
Overall length ²⁾	mm	1,882	1,882	2,326	2,291	2,342	2,175	2,533	2,565	2,563	2,553	2,968
Overall width	mm	989	989	1,438	1,368	1,508	1,083	1,648	1,560	1,643	1,332	1,612
Max.Jaw opening	mm	366	620	903	797	893	503	1,119	983	1,008	573	676
Cutter blade length	mm	319	200	237	355	237	348	240	461	240	563	631
Required oil flow	lpm	100 -180 100 -180		150 - 250			200 - 300			280 - 36		
Max.operating pressure	bar	350	350	350			350			350		
Crushing force(tip)	tonnes	65	60	68	70	64	80	95	101	103	104	178
Applicable carrier weight	tonnes	9 - 14	9 - 14	20 - 28		28 - 36			36 - 47			
Standard features												
- Hyd. Swivel motor		Star	ndard	Standard		Standard			Standar			
- Speed-up-valve		Star	andard Standard		Standard			Standar				

 Total weight including speed-up and hydraulic rotation, but excluding mounting adapter, hydraulic hoses, fitting and mounting pins. 2) The maximum length excluding mounting adapter with jaws fully closed (or opened) * Materials and specifications are subject to change without prior notice.

Specifications

ltem	Unit	EHP16	EHP19	EHP22	EHP32	
Working weight ¹⁾	kg	1,100	1,375	1,890	2,745	
Overall length ²⁾	mm	1,656	1,985	2,206	2,388	
Jaw width(Fixed/Moving Jaw)	mm	384 / 330	438 / 350	470 / 346	532 / 370	
Max.Jaw opening	mm	680	732	889	1,061	
Max.operating pressure	bar	350	350	350	350	
Crushing force(tip)	tonnes	51	54	64	78	
Cutter blade length	mm	240	240	360	360	
Required oil flow	lpm	100 - 180	150 - 250	150 - 250	200 - 300	
Applicable carrier weight	tonnes	13 - 20	16 - 25	20 - 28	28 - 36	
Standard features						
- Speed-up-valve		Not available	Standard	Standard	Standard	
Bolting tooth		Not available	Not available	Standard	Standard	


1) Total weight including speed-up and hydraulic rotation, but excluding mounting adapter, hydraulic hoses, fitting and mounting pins.

2) The maximum length excluding mounting adapter with jaws fully closed (or opened) * Materials and specifications are subject to change without prior notice.

Specifications

ltem	Unit	EHP16R	EHP20R	EHP25R	EHP35R	
Working weight ¹⁾	kg	1,250	1,780	2,300	2,950	
Overall length ²⁾	mm	1,840	2,078	2,474	2,686	
Jaw width(Fixed/Moving Jaw)	mm	384 / 330	483 / 350	470 / 346	532 / 370	
Max.Jaw opening	mm	720	732	925	1,056	
Max.operating pressure	bar	350	350	350	350	
Crushing force(tip)	tonnes	51	56	67	78	
Cutter blade length	mm	240	240	360	360	
Required oil flow	lpm	100 - 180	150 - 250	150 - 250	200 - 300	
Applicable carrier weight	tonnes	13 - 16	17 - 25	20 - 27	28 - 36	
Standard features						
- Speed-up-valve		Not available	Standard	Standard	Standard	
Bolting tooth		Not available	Not available	Standard	Standard	

 Total weight including speed-up and hydraulic rotation, but excluding mounting adapter, hydraulic hoses, fitting and mounting pins. 2) The maximum length excluding mounting adapter with jaws fully closed (or opened) * Materials and specifications are subject to change without prior notice.





www.everdigm.com

* Specifications contained in the catalogue may be changed without prior notice for improvement of quality and performance.

© EVERDIGM Corp. Printed in Korea

Distributed by

Head Office & Factory 332-3, Janggwan-ri, Jincheon-eub, Chungcheongbuk-do, Korea Tel_+82-43-530-3300 Fax_+82-530-3429

Sales & Marketing Office #1203, Woolim Lion's Valley 2, 680, Gasan-Dong, Geumcheon-Gu, Seoul, Korea Tel_+82-2-801-0800 Fax_+82-2-801-0899

